

KEMCO NQ 0712 Natural Quartz



Application area

- For new buildings and repair work in combination with KEMPERTEC, KEMPEROL and KEMPER-
- To produce an alkaline protection with the primers:
 - KEMPERTEC AC Primer,
 - KEMPERTEC EP Primer,
 - KEMPERTEC EP5 primer
- To be scattered in KEMPERDUR TC coating
- Indoor and outdoor use

Features

- Kiln-dried
- Grading curve that is adapted to the intended purpose and compatible with the system

Pack sizes

25 kg bag

Storage

Cool and dry.

CE marking

Component to 4 ETA 03/0025

ETA 03/0026 ETA 03/0043

ETA 03/0044

Consumption

As alkaline protection layer: at least 0.5 kg / m² In KEMPERDUR TC coating: at least 3 kg / m²

Application

As a scattering

See technical data sheet KEMPERDUR TC coating resp. the data sheet of the respective primer.

Application as alkaline protection

To protect the KEMPEROL Waterproofing systems against alkaline media apply a coat of KEMPERTEC EP Primer, KEMPERTEC EP5 primer or KEMPERTEC AC Primer according to TI 15 - Alkalinity. The still wet layer is scattered with KEMCO NQ 0712 Natural Quartz leaving no gaps and in grain-to-grain contact (consumption approx. $0.5 - 1.0 \text{ kg/m}^2$).

PPE

Personal protective equipment must be worn.

We recommend a hand protection and skin protection plan adapted to the workplace. Clean the tools immediately after use. KEMCO MEK Cleaning Agent.

Disposal

EAK 19 12 09 bilos No hazardous waste, disposal as domestic waste.

General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEM-PER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of



our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2019-12-11