

## KEMPEROL Roofpatch



### Uses

- For repairing leaks
- For flat and sloping surfaces

### Features

- Water vapour permeable
- Crack bridging
- Fleece-reinforced
- Cold applied
- Solvent-free
- UV resistant
- single-component
- Based on: Silane-modified polymer

### Pack sizes

41 x 27 cm in aluminium bags

5 pieces in a cardboard box

### Shelf Life

Can be stored cool, frost-free, dry and unopened. Best before: see container label.

### Properties

Colour	anthracite
Workability time *	approx. 90 min
Rainproof after *	approx. 2 h
Can be walked on after *	approx. 16 h
Cured after*	approx. 16 h

\* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

### Application

#### Preparing the substrate

The substrate must be dry, sound and free from any material that would hinder adhesion.

Only apply when the substrate and ambient temperatures are  $\geq +5$  °C.

On the following substrates, the KEMPEROL Roofpatch can be applied without primer:

Surfaces	No priming
Standard bitumen sheets	+
PVC roof sheets	+
Concrete	+
Wood	+
Screed	+
Resin-modified screed	+
Metal	+

Place the aluminium bag on a flat surface and use the side of your hand to evenly distribute the material in the bag. Take out and put on the gloves attached to the bag. Open the bag at the intended rupture aid, KEMPEROL Roofpatch remove the and apply it to the point to be sealed. Smooth out any bubbles and creases. In fresh condition, the KEMPEROL Roofpatch can be visually adjusted to the existing roof surface with slate cladding.

#### PPE

Personal protective equipment should be worn.

#### Important notice

The material safety data sheets, identification of the units, hazard warnings and safety recommendations on the units must be observed during transportation, storage and application.

The leaflets issued by the chemical industry's accident prevention and insurance association must be observed when the product is used.

#### Disposal

liquid	EAK 08 04 09
cured	EAK 08 04 10

#### General information

Times are shortened in the case of higher and are longer in the case of lower ambient temperatures and subsurface temperatures. No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

### Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2019-12-11