

according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

**KEMPERDUR AC Park** - Trade name:

- 1.2 Relevant identified uses of the substance or mixture and uses advised

Identified use: intended for professional use only!

- Application of the substance / the mixture Coating - 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: KEMPER SYSTEM GmbH & Co. KG

Holländische Strasse 32-36

34246 Vellmar

Deutschland / Germany Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110

E-Mail: MSDS@KEMPER-SYSTEM.COM

- Further information obtainable from: Research and Development

- 1.4 Emergency telephone number: Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen

Langenbeckstraße 1; Gebäude 601; 55131 Mainz

Tel. Nr.: +49 (0)6131 / 19 24 0

Universitätsmedizin der Johannes Gutenberg-Universität Mainz

## **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No

1272/2008

- Signal word

- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02

Danger

- Hazard-determining components of

labelling: methyl methacrylate 2-ethylhexyl acrylate

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

tetramethylene dimethacrylate

- Hazard statements H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

3.2 Chemical characterisation: Mixtures

- Description: Mixture: consisting of the following components.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

		(Contd. of page 1)
- Dangerous components:		
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 103-11-7 EINECS: 203-080-7 Index number: 607-107-00-7 Reg.nr.: 01-2119453158-37	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%
CAS: 42978-66-5 EINECS: 256-032-2 Index number: 607-249-00-X Reg.nr.: 01-2119484613-34	(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	2.5-10%
CAS: 8002-74-2 EINECS: 232-315-6 Reg.nr.: 01-2119488076-30	Paraffin waxes and Hydrocarbon waxes substance with a Community workplace exposure limit	0.5-2.5%
CAS: 2082-81-7 EINECS: 218-218-1 Index number: 607-134-00-4 Reg.nr.: 01-2119967415-30	tetramethylene dimethacrylate Skin Sens. 1B, H317	0.5-2.5%
- Additional information:	For the wording of the listed hazard phrases refer to section 16.	

## **SECTION 4: First aid measures**

- 4.1 Description of first aid measures

 General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints. Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

> Protect unharmed eve. If symptoms persist consult doctor.

 After swallowing: 4.2 Most important symptoms and effects.

both acute and delayed

4.3 Indication of any immediate medical

attention and special treatment needed

No further relevant information available.

No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media

- After skin contact:

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

No further relevant information available.

- Protective equipment: Do not inhale explosion gases or combustion gases.

- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation Keep away from ignition sources. Wear protective clothing. Avoid contact with skin and eyes

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

- 6.3 Methods and material for containment

and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

6.4 Reference to other sections
 See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. of page 2)

# **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- Information about fire - and explosion

protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

- 7.2 Conditions for safe storage, including any incompatibilities

Storage:

- Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

- Information about storage in one common

storage facility:

Store away from foodstuffs.

Store away from water.

- Further information about storage

conditions:

Protect from frost. Store in dry conditions.

Store in cool, dry conditions in well sealed receptacles.

Recommended storage temperature: 10-30 ℃

- Storage class:

7.3 Specific end use(s)
 No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

- Additional information about design of

technical facilities:

No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

8002-74-2 Paraffin waxes and Hydrocarbon waxes

WEL Short-term value: 6 mg/m<sup>3</sup>

Long-term value: 2 mg/m<sup>3</sup>

Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to EN 141

- Protection of hands:



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III. Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

- **Material of gloves** Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

(Contd. of page 3)

- Penetration time of glove material The determined penetration times according to EN 374 part III are not performed under practical

conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

recommended.

- As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): <10

- Eye protection:

- Body protection:

Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

Protective work clothing Impervious protective clothing

# **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid Colour: Light grey - Odour: Characteristic Not determined. **Odour threshold:** - pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

- Flash point: 10 °C

- Flammability (solid, gas): Not applicable. - Ignition temperature: Not determined.

- Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Explosion limits:** 

Lower:

Not determined. Upper: Not determined. - Density at 20 °C: 0.97 g/cm<sup>3</sup> Relative density Not determined. Vapour density Not determined. - Evaporation rate Not determined.

- Solubility in / Miscibility with

Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water:

Not determined.

Viscosity:

Dynamic at 20 °C: 320 mPas Kinematic: Not determined.

- Solvent content:

VOC (EC) 4 40 %

- 9.2 Other information No further relevant information available

# **SECTION 10: Stability and reactivity**

- 10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions

No dangerous reactions known.

- 10.4 Conditions to avoid

- 10.5 Incompatible materials:

No further relevant information available. No further relevant information available.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 4)

# **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met

- Acute toxicity Based on available data, the classification criteria are not met.		Based on available data, the classification chiefla are not met.			
- LD/LC50	- LD/LC50 values relevant for classification:				
80-62-6 m	80-62-6 methyl methacrylate				
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>5000 mg/kg (rabbit)			
Inhalative	LC50/4 h	29.8 mg/l (rat)			
103-11-7 2-ethylhexyl acrylate					
Oral	LD50	4435 mg/kg (rat) (IUCLID)			
Dermal	LD50	7522 mg/kg (rabbit) (IUCLID)			
42978-66-5 (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate					
Oral	LD50	2000 mg/kg (rat) (OECD 423)			
Dermal	LD50	2000 mg/kg (rabbit) (OECD 402)			
8002-74-2 Paraffin waxes and Hydrocarbon waxes					
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>2000 mg/kg (rat)			
2082-81-7	2082-81-7 tetramethylene dimethacrylate				
Oral	LD50	10066 mg/kg (rat) (OECD 401)			
Dermal	LD50	>3000 mg/kg (rabbit)			

- Primary irritant effect:

- **Skin corrosion/irritation** Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation May cause an allergic skin reaction.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 May cause respiratory irritation.

STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- 12.1 Toxicity	
- Aquatic toxicity:	
80-62-6 methyl m	ethacrylate
NOEC	37 mg/l (Daphnia magna) (21 days; OECD 202 Part 2, flow)
EC3	37 mg/l (Scenedesmus quadricauda) (DIN 38412 Part 9; 8d)
EC0	100 mg/l (Pseudomonas putida)
EC50	69 mg/l (Daphnia magna) (48 h; OECD 202)
LC 50	>79 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96 h; OECD 203)
103-11-7 2-ethylh	exyl acrylate
Inhalative LC50/8	h 1.19 mg/l (rat) (OECD 403)
EC50	17 mg/l (Daphnia magna) (48h; IUCLID)
EC50	> 10000 mg/l (Pseudomonas putida) (30 min.; IUCLID)
IC50	44 mg/l (DESMODESMUS SUBSPICATUS) (72h, IUCLID)
LC50	23 mg/l (Leuciscus idus (Goldorfe)) (48h; IUCLID)
42978-66-5 (1-me	thyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate
LC50	4.6 - 10 mg/l (Leuciscus idus) (96h; DIN38412- Teil 15)
EC50	> 1000 mg/l (Belebtschlamm) (3h, OECD 209)
EC50	89 mg/l (Daphnia magna) (48h; US EPA)
EC50	65.9 mg/l (DESMODESMUS SUBSPICATUS) (72h; DIN 38412 Teil 9)
EC10	6.6 mg/l (DESMODESMUS SUBSPICATUS) (72h)
2082-81-7 tetram	ethylene dimethacrylate
EC50	9.79 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)
	32.5 mg/l (Idus melanotus) (48h; OECD 203)
L	(Contd. on page 6)

Contd. on page (



according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

- 12.2 Persistence and degradability
 - 12.3 Bioaccumulative potential
 - 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

- Ecotoxical effects:

- Remark: Harmful to fish

- Additional ecological information:

- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment

- PBT: Not applicable.- vPvB: Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods

- **Recommendation** Disposal according to official regulations

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

- **14.1 UN-Number** - **ADR, IMDG, IATA** UN1993

- 14.2 UN proper shipping name

- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER,

STABILIZED

- IMDG, IATA FLAMMABLÉ LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER,

П

STABILIZED)

- 14.3 Transport hazard class(es)

- ADR



- Class 3 (F1) Flammable liquids.

- Label 3

- IMDG, IATA



- Class 3 Flammable liquids.

- Label 3

- 14.4 Packing group

- ADR, IMDG, IATA

- 14.5 Environmental hazards: Not applicable.

- **14.6 Special precautions for user** Warning: Flammable liquids.

- Danger code (Kemler):

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

	(Contd. of page 6
- EMS Number: - Stowage Category	F-E, <u>S-E</u> B
- 14.7 Transport in bulk according to Annex II of Ma Code	rpol and the IBC  Not applicable.
- Transport/Additional information:	ivot applicable.
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- Transport category - Tunnel restriction code	2 D/E
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. P5c FLAMMABLE LIQUIDS Seveso category

- Qualifying quantity (tonnes) for the

application of lower-tier requirements 5,000 t - Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX** 

- National regulations:

- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.

Conditions of restriction: 3

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning women of child-bearing age must be observed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS: research & development Product Management

**Product Management** Contact:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International - Abbreviations and acronyms:

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 8)

(Contd. of page 7)



- Sources

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.06.2017 Version number 1 Revision: 22.06.2017

Trade name: KEMPERDUR AC Park

Internet:

- www.echa.com
- www.baua.de
- www.gestis.itrust.de (IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance)