

KEMPEROL UP-I inhibitor



Uses

- For extension the processing time for the sealings KEMPEROL V 210 M and KEMPEROL BR M at ambient temperatures higher than 25 °C.

Pack sizes

0,3 kg in a container

Shelf Life

Can be stored cool, frost-free, dry and unopened. Best before: see container label.

Usage guide

0.3 kg for 20 kg KEMPEROL V 210 M resp. KEMPEROL BR M Sealing.

CE marking

Component to 2	ETA 03/0025
	ETA 03/0026

Properties

Form	Liquid
------	--------

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Application

KEMPEROL UP-I Inhibitor to be mixed with a stirring stick or slow-running agitator intensively into the resin component until you achieve a homogeneous and streak-free mixture. In the case of V 210 M and BR M Stir directly into the liquid seal KEMPEROL CP catalyst powder before the is added. Mixing time is approx 1 minute.

The storage suitability of component B is not shortened due to the addition of KEMPEROL UP-I inhibitor .

PPE

Personal protective equipment should be worn. We recommend a hand protection and skin protection plan adapted to the workplace. Clean the tools immediately after use with KEMCO MEK Cleaning Agent.

Note

Please consider Technical Information TI 23 - solvent-based products.

Important notes

The safety data sheets, identification of the containers, hazard statements and the safety recommendations on the containers must be observed during transportation, storage and application. The BG-Chemie technical data sheets must be observed during application.

Disposal

Inhibitor	liquid	EWC 07 01 04
-----------	--------	--------------

General information

Times are shortened in the case of higher and are longer in the case of lower ambient temperatures and subsurface temperatures. No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of

our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2021-03-15