

according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

KEMPERTEC 1K Thinner - Trade name:

 1.2 Relevant identified uses of the substance or mixture and uses advised

Identified use: intended for professional use only!

- Application of the substance / the mixture Thinner, Diluent

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: KEMPER SYSTEM GmbH & Co. KG

Holländische Strasse 32-36

34246 Vellmar

Deutschland / Germany Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110 E-Mail: MSDS@KEMPER-SYSTEM.COM

- Further information obtainable from: research & development

- 1.4 Emergency telephone number: Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen

Langenbeckstraße 1; Gebäude 601; 55131 Mainz

Tel. Nr.: +49 (0)6131 / 19 24 0

Universitätsmedizin der Johannes Gutenberg-Universität Mainz

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 $\hbox{H335-H336} \ \ \hbox{May cause respiratory irritation. May cause drowsiness or dizziness}.$

H304 May be fatal if swallowed and enters airways. Asp. Tox. 1 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No

1272/2008 Hazard pictograms The product is classified and labelled according to the CLP regulation.



GHS02



GHS07





- Signal word Danger

- Hazard-determining components of

labelling:

hydrocarbons, C9, aromatic

- Hazard statements Flammable liquid and vapour. H226

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures

- Description: Mixture: consisting of the following components.

- Dangerous components:

EC number: 918-668-5 hydrocarbons, C9, aromatic

Reg.nr.: 01-2119455851-35 Flam. Lig. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336

(Contd. on page 2)

50-100%





according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

Trade name: KEMPERTEC 1K Thinner

(Contd. of page 1)

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

Immediately wash with water and soap and rinse thoroughly. Seek medical treatment in case of complaints.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. - After eye contact:

Protect unharmed eye.

- After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects,

both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

After skin contact:

 Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

- 5.3 Advice for firefighters

- Protective equipment:

Additional information

Formation of toxic gases is possible during heating or in case of fire.

Do not inhale explosion gases or combustion gases. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective

equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation Keep away from ignition sources.

- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

6.3 Methods and material for containment

- 6.4 Reference to other sections

and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

(Contd. on page 3)

(Contd. of page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

Trade name: KEMPERTEC 1K Thinner

- Information about storage in one common

storage facility:

Store away from foodstuffs.

Further information about storage conditions:

Protect from frost.
Store in dry conditions.

Keep container tightly sealed. Recommended storage temperature: 10-30 °C

- Storage class:

- 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of

technical facilities:

No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to EN 141

- Protection of hands:

III S

Protective gloves

Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion

and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: $\geq 0.5 \ mm$

- Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical

conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

recommended.

- As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): <10

- Eye protection:



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

- Body protection: Protective work clothing

Impervious protective clothing

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid Colour: Colourless

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

Trade name: KEMPERTEC 1K Thinner

	(Contd. of page 3)
- Odour: - Odour threshold:	Aromatic Not determined.
- pH-value:	Not determined.
- Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. Undetermined.
- Flash point:	47 °C
- Flammability (solid, gas):	Not applicable.
- Ignition temperature:	
Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not selfigniting.
- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Explosion limits: Lower: Upper:	Not determined. Not determined.
- Density at 20 °C: - Relative density - Vapour density - Evaporation rate	0.87 g/cm³ Not determined. Not determined. Not determined.
- Solubility in / Miscibility with water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity: Dynamic: Kinematic at 23 °C:	Not determined. 0,9 mm ² /s
- Solvent content: VOC (EC) - 9.2 Other information	100.00 % No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be

avoided:

- 10.3 Possibility of hazardous reactions

- 10.4 Conditions to avoid

- 10.5 Incompatible materials: - 10.6 Hazardous decomposition products:

No decomposition if used according to specifications. No dangerous reactions known.

No further relevant information available. No further relevant information available. No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

hydrocarbons, C9, aromatic

LD50 >3,492 mg/kg (rat) (OECD 401) Dermal LD50 >3,160 mg/kg (rabbit) (OECD 402)

Primary irritant effect:

- Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met. - Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met. - Carcinogenicity Based on available data, the classification criteria are not met. - Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness. - STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

Trade name: KEMPERTEC 1K Thinner

May be fatal if swallowed and enters airways.

(Contd. of page 4)

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

- Aspiration hazard

hydrocarbons, C9, aromatic

LL 50 9.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)

EL50 2.9 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)

3.2 mg/l (Daphnia magna) (48h; OECD 202)

EC50 >99 mg/l (Belebtschlamm) (10 min.; OECD 209)

- 12.2 Persistence and degradability

No further relevant information available. - 12.3 Bioaccumulative potential No further relevant information available. - 12.4 Mobility in soil No further relevant information available.

- Ecotoxical effects:

Toxic for fish - Remark:

- Additional ecological information:

 General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment

Not applicable. Not applicable. - vPvR

- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal according to official regulations

- European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number

- ADR, IMDG, IATA UN3295

- 14.2 UN proper shipping name

- ADR 3295 HYDROCARBONS, LIQUID, N.O.S., ENVIRONMENTALLY HAZARDOUS - IMDG HYDROCARBONS, LIQUID, N.O.S. (hydrocarbons, C9, aromatic), MARINE

POLITITANT - IATA HYDROCARBONS, LIQUID, N.O.S.

- 14.3 Transport hazard class(es)

- ADR



- Class 3 (F1) Flammable liquids.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

Trade name: KEMPERTEC 1K Thinner

(Contd. of page 5) - Label - IMDG Class 3 Flammable liquids. Label - IATA - Class 3 Flammable liquids. Label - 14.4 Packing group - ADR, IMDG, IATA Ш - 14.5 Environmental hazards: Product contains environmentally hazardous substances: hydrocarbons, C9, aromatic - Marine pollutant: Symbol (fish and tree) Symbol (fish and tree) Special marking (ADR): - 14.6 Special precautions for user Warning: Flammable liquids. - Danger code (Kemler): - EMS Number: F-E,S-D - Stowage Category Α 14.7 Transport in bulk according to Annex II of Marpol and the IBC Not applicable. Transport/Additional information: Limited quantities (LQ) - Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml - Transport category - Tunnel restriction code D/E - IMDG Limited quantities (LQ) 5L - Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml - UN "Model Regulation": UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III, ENVIRONMENTALLY **HAZARDOUS**

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I

Seveso category

None of the ingredients is listed.

E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the

application of lower-tier requirements Qualifying quantity (tonnes) for the

application of upper-tier requirements - REGULATION (EC) No 1907/2006 ANNEX 200 t 500 t

Conditions of restriction: 3

National regulations:

- Information about limitation of use: Employment restrictions concerning juveniles must be observed.

(Contd. on page 7)





according to 1907/2006/EC, Article 31

Printing date 18.10.2017 Version number 2 Revision: 18.10.2017

Trade name: KEMPERTEC 1K Thinner

(Contd. of page 6)

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning women of child-bearing age must be observed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship

- Relevant phrases H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

- Department issuing SDS: research & development

 Contact: research & development

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- Sources Internet:

www.echa.com - www.baua.de

- www.gestis.itrust.de (IFA: Institute für Occupational Safety and

Health of the German Social Accident Insurance)

- * Data compared to the previous version altered.